



PF310

Euro profile cylinders
key / key
in sizes 26mm x 26mm
to 70mm x 70mm and all
sizes in between

Available in Pro-Snap



PF330

Euro profile cylinders
key / thumb turn
in sizes 26mm x 26mm
to 70mm x 70mm and all
sizes in between

Available in Pro-Snap



PF391-11

Indicating euro cylinder
for use on toilet doors

Standard sizes are
31mm x 31mm or
35mm x 35mm



PF352

Half euro cylinder with
indexable cam (cam can
be moved to any of 8
positions)

This cylinder also suits
ABUS padlock 86TI55



PF396-1031

Half euro cylinder thumb
turn operated

Ideal for rear patio doors
to stop cylinder being
snapped



PF392-VHS83

"Snowman" cylinder

Insert for use on ABUS
83 range padlocks



PF310-356

Standard rim cylinder to
suit 32mm hole

Supplied with solid
brass rose



PF310-3560425

Threaded cylinder

Supplied 1 per box
(not pairs)

Several lengths
available



PF3560224

Heavy duty cam lock

Suitable for use on
Securikey key cabinets



PF357-1

Scandinavian half oval
interior cylinder



PF357-2

Scandinavian half oval
exterior cylinder

This cylinder also suits
ABUS padlock "83"
range



PF353

Key safe
This stainless steel lock-
able tube is designed to
be cemented into a wall.



PF310-380

50mm brass padlock

Available sub assembled ready to be keyed up to customers key



PF310-380SALT

50mm brass padlock salt water resistant

Available sub assembled ready to be keyed up to customers key



PF310-380HB64

50mm brass padlock 64mm long shackle

Available sub assembled ready to be keyed up to customers key



PF310-380HB80

50mm brass padlock 80mm long shackle

Available sub assembled ready to be keyed up to customers key



TOOLS

A full range of tools and pinning kits are available to get the most from this product

This allows the locksmith to re-key, key alike and masterkey the range

PFAFFENHAIN PRO-SNAP

This range of cylinders has been developed to combat the real problem of cylinder snapping

The cylinders are pre disposed to snapping 10mm from the outside edge of the euro cylinder leaving the cam protected

This feature is available on any size of cylinder from 26mm x 26mm key / key upwards and 31mm x 31mm upwards on a key / thumbturn cylinder

