



GMK RANGE

8 lever key operated safe conforming to EN 14450-S2

Base and back fixing holes complete with anchor fixing bolts

Excellent value / security ratio
10mm door & 5mm body

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
GMK/3	220	350	300	200	340	245	25	18
GMK/4	280	400	350	260	390	295	35.5	31
GMK/5	350	470	350	330	460	295	47.5	47
GMK/6	430	490	350	410	480	295	56	60
GMK/7	490	430	400	470	420	345	61	70



GMT RANGE

Combination safe with mechanical key over-ride conforming to EN 14450-S2

Base and back fixing holes complete with anchor fixing bolts

10mm door & 5mm body

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
GMT/3P	220	350	300	200	340	245	25	18
GMT/4P	280	400	350	260	390	295	35.5	31
GMT/5P	350	470	350	330	460	295	47.5	47
GMT/6P	430	490	350	410	480	295	56	60
GMT/7P	490	430	400	470	420	345	61	70



GMK/4 SLOT

Safe with deposit slot

8 lever key operated safe conforming to EN 14450-S2

Excellent value / security ratio

10mm door & 5mm body

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
GMK/4SLOT	280	400	350	260	390	295	35.5	31



GTR RANGE

Safe with deposit slot

Time delay feature

Digital electronic lock conforming to EN 1300

Mechanical key over-ride

Mains adaptor supplied

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
GTR/4P	280	400	350	260	390	295	35.5	31
GTR/6P	430	490	350	410	480	295	56	60





DPK RANGE

Fire resistant 30 mins according to EN 15659

S2 burglary to EN 14450

10mm thick door

8 lever key pick resistant

Twin wall construction with fire resistant material between walls



DPE RANGE

Fire resistant 30 mins according to EN 15659

S2 burglary to EN 14450

10mm thick door

Mechanical over-ride

Twin wall construction with fire resistant material between walls

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
DPK/4	280	400	355	170	305	245	34	12.7
DPK/5	350	490	430	240	380	310	51.5	29.8
DPK/7	490	430	430	380	330	310	63.5	39.5

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
DPE/4	280	400	355	170	305	245	34	12.7
DPE/5	350	490	430	240	380	310	51.5	29.8
DPE/7	490	430	430	380	330	310	63.5	39.5



GT RANGE

Digital electronic wall safe with 10mm laser cut door with shelf and fixings

Emergency over-ride by means of physical high security double bit key

9v power over-ride on door



SS RANGE

Economy key operated wall safe

Double bitted key

SS/3 in 3 depths

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
GT/3P	210	340	200	185	315	150	13	9
GT/4P	270	390	200	245	365	150	18	14
GT/5P	340	460	200	315	435	150	25	21
GT/6P	420	480	230	395	455	180	33.5	33
GT/7P	480	420	280	455	395	230	34.5	43
GT/7LP	480	420	360	455	395	310	27	57

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
SS/1	210	270	150	185	245	100	8	5
SS/2	210	270	200	185	245	150	8.5	7
SS/3	210	340	150	185	315	100	10	6.5
SS/3B	210	340	200	185	315	150	10.5	9
SS/3C	210	340	100	185	315	50	10	2.9
SS/4	210	390	200	245	365	150	16.5	14





ACH RANGE

Domestic / light duty commercial safe

6 lever double bitting key

Italian quality make yet economically priced

Shelf carpets and fixings included

Rounded security door

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
728/ACH	200	310	280	195	305	215	10	13
730/ACH	220	350	300	215	345	235	13.5	19
745/ACH	200	400	450	195	395	385	16	30



AMP RANGE

Electronic combination hotel safe

Motorized bolts on rounded security door

Shelf carpet and fixings included

With power code and key over-ride features

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
728/AMP	200	310	280	195	305	215	10	13
730/AMP	220	350	300	215	345	235	13.5	19
745/AMP	200	400	450	195	395	385	16	30



SMK/8

8mm laser cut door with 4mm body key safe

2 internal shelves

Ideal for controlled drugs and first aid applications

8 lever anti-pick lock

Fixing bolts supplied

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
SMK/8	600	430	400	590	420	350	56	85



SMT8/P

8mm laser cut door with 4mm body key safe

2 internal shelves

Ideal for controlled drugs and first aid applications

Electronic combination locking with over-ride key

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
SMT8/P	600	430	400	590	420	350	56	85



ALP RANGE

Electronic combination hotel safe

Manually retracting bolts on rounded security door

Shelf carpet and fixings included

With power code and key over-ride features



MB/0

MB/0 is a small safe which can be fitted as free standing or as a wall safe

Ideal for concealment of small items or keys

Available in a version with slot as an alms box for collecting donations
Keyed alike or to differ

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
728/ALP	200	310	280	195	305	215	10	13
730/ALP	220	350	300	215	345	235	13.5	19
745/ALP	200	400	450	195	395	385	16	30

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
MB/0	130	220	120	125	215	90	4	2.5



CK RANGE

Key operated key safes

2 sizes 40 hook and 120 hook

Laser cut 8mm door and 3mm body

Metal fixed key hooks

120 hook achieved by internal rotating leaf



CE RANGE

Electronic combination key safes with 6 lever mechanical over-ride key

40 hook and 120 hook

Laser cut 8mm door and 3mm body

120 hook achieved by internal rotating leaf

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
CK/40	470	360	140	460	350	120	25	20
CK/120	470	360	140	460	350	120	27	20

EXTERNAL

INTERNAL

	H	W	D	H	W	D	Kg	Lt
CE/40	470	360	140	460	350	120	25	20
CE/120	470	360	140	460	350	120	27	20



HS400SC

Gun safe with key operated lock
 Internal locking coffers for ammunition
 50mm door thickness including lock panel with a body of 2mm steel construction
 Holds up to 7 rifles

EXTERNAL

	H	W	D	Kg	Lt
HS400SC	1560	365	320	54	148



HS600SC

Gun safe with key operated lock
 Internal locking coffers for ammunition
 50mm door thickness including lock panel with a body of 2mm steel construction
 Holds up to 11 rifles

EXTERNAL

	H	W	D	Kg	Lt
HS600SC	1560	535	320	70	218



4430

Viro key operated gun safe for 3 rifles
 Internal shelf
 Double bitted 6 lever key

EXTERNAL

	H	W	D	Kg	Lt
4430	1500	200	260	????	????



HS400SCE

Gun safe with electronic combination lock
 Internal locking coffers for ammunition
 50mm door thickness including lock panel with a body of 2mm steel construction
 Holds up to 7 rifles

EXTERNAL

	H	W	D	Kg	Lt
HS400SCE	1560	365	320	54	148



HS600SCE

Gun safe with electronic combination lock
 Internal locking coffers for ammunition
 50mm door thickness including lock panel with a body of 2mm steel construction
 Holds up to 11 rifles

EXTERNAL

	H	W	D	Kg	Lt
HS600SCE	1560	535	320	70	218



SEC90D

Master trigger lock
 Helps prevent unauthorized firing



TECHNO BLANK 5

Evo-Lock is the latest generation of EN 1300 certified high security locks fitted on a variety of Technomax safes

